

## ■ Specification

NIJI-2-1404N003-E

Model	NIJI-2 Variable wavelength light source
Light source	Xenon lamp 150W
Irradiation range	300~1150nm
Wavelength purity	5 or 10 or 20nm ( selectable when purchasing )
Irradiation intensity	More than 1mW( more than 40 $\mu$ mol/m <sup>2</sup> /s) <sup>*1</sup>
Irradiation area	More than $\Phi$ 3mm <sup>*2</sup>
Wavelength check	Indicator
Shutter	Manual
Optical fiber	$\Phi$ 3mm bundle optical fiber, Length 1M

\*1 when it is measured around 480nm

\*2 Irradiation area can be changed by changing the distance between the tip of the optical fiber and sample.

## ■ Option

### ● Si photo diode detector

This is a calibrated detector and used to measure/calculate the intensity(mW/cm<sup>2</sup>) at each wavelength.

### ● Optical fiber stand

This is a magnetic stand which hold the optical fiber.

Manufacturer

● The dimensions in the above is approximate ones. Depending on the options or etc., appearance and dimensions may be different.

● The appearance of the product and any specifications contained herein are subject to change without notification.

## ■ Dimensions ( unit: mm )



Approx. W230(242.5) × D295(350.4) × H414(441.2) mm  
\*The dimensions in ( ) is the ones including the protrusions

**BUNKOUKEIKI**  
分光計器株式会社

[http:// www.bunkoukeiki.co.jp/](http://www.bunkoukeiki.co.jp/)

Head quarter 4-8 Takakura-cho, Hachioji-shi, Tokyo 192-0033, Japan  
TEL +81-042-646-4123 FAX+81-42-644-3881

# NIJI-2 Variable Wavelength Light Source



- Irradiation in the wide range from ultraviolet , visible , to Infrared light (300~1150nm) can be covered.
- Stand-alone and compact design require only a modest requirement of bench space for installation
- The built-in wavelength indicator make the operation easy and comfortable.

**BUNKOUKEIKI**  
分光計器

# NIJI-2 Variable wavelength light source




Generally, the irradiation light source configured with a xenon lamp and band pass filter is cheaper while it is not convenient since the irradiation wavelength cannot be selected without any restriction and different filters have to be prepared to use different wavelengths. The Model NIJI 2 Variable Wavelength Light Source is capable to perform irradiation at any wavelength in the range of 300~1150nm using the monochromator instead of the band pass filter. In the past, the light source with the monochromator had a disadvantage over that with band pass filter since it reduce intensity of the light. Development of our new optical system in the monochromator for the model NIJI 2 has overcome such technical problem and has been successful in generated monochromatic light with high output of intensity such as more than 1mW ( at 480nm).

## Major application

- Photocatalysis**  
 Photochemical reaction  
 As a strong light source for photocatalyst and photochromic compound, any wavelength in the range of 300~1150nm can be selected and its monochromatic light can be irradiated.
- Evaluation of spectral characteristic of the solar cells**  
 Evaluation of spectral characteristic the CCD and photo sensors  
 As a light source for a photoelectric conversion device, any wavelength in the range of 300~1150nm can be selected and its monochromatic light can be irradiated.
- Photo simulation**  
 Photosynthetic reaction  
 Cell activation by light illumination can be analyzed and also effective wavelength for photosynthetic reaction can be selected and irradiated.
- Light source for illumination**  
 Light source for a microscope  
 As a light source for monochromatic illumination and fluorescence excitation light source for a microscope, the Model NIJI as a light source is very effective.

## High output monochromatic light irradiation with more than 1mW




When wavelength purity was selected at 20nm with Φ3mm bundle fiber and total luminous flux entered.


Monochromatic light in the range of ultraviolet, visible, and Infrared (300~1150nm) can be irradiated with high output intensity. Using a bundle filter on the outlet of the system, irradiation area can be adjusted for various applications.

## Turning the dial, irradiation wavelength can be selected

By turning the dial, you can choose the wavelength with 0.1nm step for irradiation.




## Wavelength indicator makes the operation easy and comfortable



When selecting the wavelength at 600nm for an example, the wavelength indicator lights if there is any problem on the system.

## Compact system requires minimum installation space



Conventional system consists of a xenon lamp, optical system and monochromator separately. The NIJI-2 is an integrated system which require minimum installation space. The system is stand-alone so that no PC is required. Compact and light weight design allow the customer to transport the system easily with a handle.